

DOTLUX Standardnetzteil für DOTLUX LED-Panel 50 Watt 1200mA (für Art. 3572-040120)

Order number: 3574

Power consumption in watts: 50; protection class (IP): IP20; Input voltage: 220 - 240 V AC; Output current in A: 1,25; Power Factor: 0,95; Tc temperature in °C: 80; Protection class: II; Suited for emergency lighting: yes; Output voltage: 27 - 42 DC; Input voltage span: 220-240 V AC; Warranty in years: 5; Suited for emergency power: -; Input voltage range luminaire: 220-240 V AC; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Suitable for emergency lighting: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; LED-Betriebsstrom in mA: 1200
width: 53mm