

DOTLUX LED-Downlight CIRCLEugr 21W 3000/4000/5700K COLORselect (ohne Netzteil)

Order number: 3842-140090

- + Blendfreies Leuchtendesign (UGR < 19)
- + Facierter Mulit-Reflektor sorgt für gleichmäßige Ausleuchtung
- + Werkzeugloser Klemmenanschluss (durchverdrahtbar mit integrierter Zugentlastung)
- + Spritzwassergeschütztes Gehäusedesign (IP 54 Frontseitig)
- + SmartCooling: raumseitige Wärmeableitung durch Aluminiumreflektor
- + Abstandsfreie Montage möglich
- + Für Zentralbatterie geeignet

Power consumption in watts: 25; Net luminous flux in lumens: max.2650; Beam angle: 90; protection class (IP): IP54; Light color: multicoloured; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Frequency range in Hz: 50/60; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; Protection class: II; Voltage type: AC; Housing colour: white; Glare-free: UGR < 19; Installation opening diameter in mm: 200-210; Warranty in years: 5; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; Light colour according to EN 12464-1: warm white <3300 K; LED-Betriebsstrom in mA: 700
diameter: 228mm