

DOTLUX BASIS LUNA 490mm B-goods

Order number: 4613-B-Ware

- Base for LUNA 490mm

Power consumption in watts: 36; Net luminous flux in lumens: max. 3500; Beam angle: 160; protection class (IP): IP44; Input voltage: 220 - 240 V AC; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,97; Inrush current in A: 0; Switch cycles: > 100.000; Warranty in years: 0; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; Light colour according to EN 12464-1: warm white <3300 K; LED-Betriebsstrom in mA: 900
diameter: 460mm