

DOTLUX Construction site floodlight WORKERrocket 70W 5000K CRI>92 IP54 IK07

Order number: 5353-050360

- Easy to transport thanks to compact design and an ergonomic carrying handle
- High stability thanks to integrated tripod guarantees safe work
- 2 m flexible H07RNF - rubber cable for optimal use on the construction site or outdoors
- Integrated cable holder
- Additional socket IP 54 maximum 1800 Watt / 230 Volt /16A
- Glare-free all-round lighting with 360° beam angle
- Most natural color rendering CRI >92 for demanding users
- Splash-proof housing IP 54

Lumen per watt: 86; Power consumption in watts: 70; Net luminous flux in lumens: 6000; Beam angle: 360; protection class (IP): IP54; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 30.000 h at 25°C; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 92; Inrush current in A: 0; IK protection: IK07; Lumen per watt: 86; Protection class: I; Housing colour: multicoloured; Warranty in years: 2; L80/B10: 22500; Energy efficiency class according to EU regulation 2019/2015: not required; Mounting location: Indoor + covered outdoor; Lifetime L80/B10 at 25°C: 22500; LED-Lifetime light source L70/B50 at 25°C: 45000; ETIM Gruppen-ID: EC000346; With illuminant: Yes; Impact strength: IK07; Suitable for lamp power in w: 63.5; Lifetime L70/B50 at 25°C: 45000; Lifetime L90/B10 at 25°C: 11250; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Lamp type: Other; Connection type: Other
width: 636mm