

DOTLUX LED EX protective light MISTRALex EX Protected IP66 1272mm 44W 4000K IK10 Zone 2 & 22 DALI

Order number: 6007-040140

- UV-stable, shatterproof IK10/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
- Stainless steel catches with integrated anti-theft device
- Can be wired through with an internal 3-pole luminaire connection terminal
- Now supplied with two ATEX cable glands (incl. one dummy plug)
- Silicone-free, also for paint shops
- Suitable for central battery
- DALI dimmable
- ATEX certified
- Explosion group:
 - II 3 G Ex ec IIC T6 Gc
 - II 3 D Ex tc IIIC T85°C Dc IP66
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in flammable locations (DIN EN 60598-2-24, VDE 0711-2-24)
- Sustainable product design thanks to easily replaceable components

Net luminous flux in lumens: 6710; Lumen per watt: 153; Power consumption in watts: 44; Beam angle: 140; protection class (IP): IP66; Light color: white; Input voltage: 186 - 240 AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; IK protection: IK10; Lumen per watt: 153; Protection class: I; Warranty in years: 7; ENABLED licensed product: Yes; Assortment: Highline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: E0001952; Material cover: Plastic matt/satinized; Impact strength: IK10; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D
width: 145mm