

DOTLUX LED-Lichtbandsystem LINEAcompact 50W breitstrahlend 1452mm 4000K nicht dimmbar B-Ware

Order number: 4942-040160-B-Ware

Lumen per watt: 167; Power consumption in watts: 50; Net luminous flux in lumens: 8350; Beam angle: 160; protection class (IP): IP54; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,98; Lumen per watt: 167; Protection class: I; Voltage type: AC; Switch cycles: > 100.000; Input voltage span: 220-240 V AC; Warranty in years: 0; Input voltage range luminaire: 220-240 V AC; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Group Identification Number: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No