

DOTLUX LED bollard light WAY 55cm 7.5/15W 4000K

Order number: 4559-040360

Dotlux LED bollard light WAY 55 cm

- Freely selectable light emission area due to interchangeable glass and cover plates
- Power-Select allows the adjustment of the system power 50% / 100%
- High-quality aluminum housing with powder coating in DB703
- Glare-free and homogeneous light distribution with high color rendering Ra>82
- EasyMount platform enables simple and fast installation
- For looping through with connection box (input and output each for 3 x 2.5 mm² cable)
- Mounting base made of special aluminum alloy, approved for installation with ground contact

Power consumption in watts: 7,5-15; Net luminous flux in lumens: 400/800; Lumen per watt: 53; Beam angle: 360; protection class (IP): IP65; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: approx. 40.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Inrush current in A: 0; IK protection: IK06; Lumen per watt: 53; Protection class: I; Housing colour: gray; Warranty in years: 5; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC000062; Material cover: Plastic, structured; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK06; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: E
width: 120mm