

DOTLUX LED bottle light GINI RGBW

Order number: 600194

- Dimmable LED bottle light with 7 hours of light duration and over 14 different light colors thanks to RGBW
- Compatible with a wide range of standard and screw-top bottles
- Food-safe silicone stopper fits a wide variety of bottle necks
- Includes 1.5m USB-C charging cable, charging time approx. 6 hours
- Decorative use indoors and outdoors thanks to IP44 rating
- Long service life with built-in 3600mAh Li-Ion battery

Product functions:

- Switch on with a brief touch, the warm white color lights up
- Another short touch, the light switches to automatic color change mode
- A short touch changes the light colors
- Dimmable with a long touch

Lumen per watt: 70; Power consumption in watts: 3; Net luminous flux in lumens: 210; Beam angle: 120; Light color: RGBW; Service life: approx. 30.000 h at 25°C; Color temperature in Kelvin: 2700; Color-rendering-index: CRI > 82; Power Factor: 0,5; Battery runtime: 7; Lumen per watt: 70; Protection class: III; Voltage type: DC; Housing colour: black; Suited for emergency lighting: No; Switch cycles: > 60.000; Warranty in years: 2; L80/B10: 30000; Dimming without dimmer: No; ENABLED licensed product: Yes; Energy efficiency class according to EU regulation 2019/2015: -; Lifetime L80/B10 at 25°C: 30000; LED-Lifetime light source L70/B50 at 25°C: 60000; ETIM Gruppen-ID: EC000300; With illuminant: Yes; Suitable for workplace according to EN 12464-1: Yes; Suitable for number of light sources: 0; With control gear: No; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: Yes; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: Yes; Dimming Zigbee: No; Dimming with push-button: Yes; No dim function: No; Light distributor: Diffuser lens/optic/panel; Colour consistency (McAdam ellipse): SDCM6; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: No; Constant light output (CLO): No; Photobiological safety according to EN 62471: RG0; Colour of light adjustable: Positions; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Electrical connection with connector system: No; Luminaire heads flexible: No; Direct-/indirect proportion separately controllable: No; Adjustable: Yes; Exchangeable control gear: No; Suitable for lamp power in w: 3; Lamp type: LED; With dimmer: Yes; With presence indicator: No; With reflector: No; With switch: No; With separate reading light: No; Material: Metal/plastic; Dimming DALI-2: No; Dimming phase cut-on: Yes; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 60000; Lifetime L90/B10 at 25°C: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: G; Beam angle adjustable: No; Light sharing: Symmetric; Luminous flux adjustable: Continuously variable; Light outlet: Indirect; Type of grid: Other; Type of control gear: Not required; Material cover: Other; Lamp holder: Other
diameter: 80mm width: 115mm