

DOTLUX LED damp-proof luminaire HIGHFORCEabs IP66/IP69 1455mm 54W 4000K IK06 2x5-pole through-wired DALI including end cap

Order number: 4779-040120-B-Ware

- UV-stable diffuser and housing
- Chemical resistant special diffuser made of ChemRST material
- Suitable for agricultural operations
- Housing made of impact-resistant polycarbonate
- IK06 impact resistance
- Suitable for central battery
- IP66 / IP69
- Decertified
- DLG certified
- Distance between both mounting brackets adjustable (700-980mm)
- Mounting brackets allow ceiling and/or wall mounting
- All HIGHFORCE lights are supplied without connector plug. You can find accessories here in the store.

Power consumption in watts: 54; Net luminous flux in lumens: 7170; Lumen per watt: 133; Beam angle: 120; protection class (IP): other IP66 / IP69; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,95; Inrush current in A: 0; IK protection: IK06; Lumen per watt: 133; Protection class: I; Housing colour: gray; Food-Ready: Yes; Warranty in years: 0; Assortment: Highline; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK06; Dimming DALI-2: Yes; Pulse duration in µs: 0
width: 90mm