

DOTLUX LED downlight CIRCLEflat 6W 4000K incl. driver set 5 pieces

Order number: 600096

- Flat design with integrated power supply unit enables use even in difficult installation locations
- Backlight technology in a robust design
- Sturdy mounting clips ensure a secure hold
- Set of 5

Lumen per watt: 65; Power consumption in watts: 6; Net luminous flux in lumens: 390; Beam angle: 120; protection class (IP): IP20; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 30.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,6; Lumen per watt: 65; Protection class: II; Housing colour: white; Switch cycles: > 60.000; Installation opening diameter in mm: 95-100; Warranty in years: 2; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC001744; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Covering of the luminaire with thermally insulating material possible: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: G; Colour of light adjustable: No
diameter: 118mm