

**DOTLUX LED downlight CIRCLEmini-AC UGR <19 5W 3000K Set 5 pieces**

Order number: 600092

- Glare-free luminaire design (UGR>19)
- Perfectly suited for refurbishments due to the low installation depth and the relatively large cover
- Easy installation thanks to the integrated power supply unit and 15 cm connection cable
- Flexible illumination thanks to swivel-mounted LED unit
- Set of 5

Lumen per watt: 80; Power consumption in watts: 5; Net luminous flux in lumens: 400; Beam angle: 40; protection class (IP): IP20; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 20.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Power Factor: 0,5; Lumen per watt: 80; Protection class: II; Housing colour: white; Glare-free: UGR < 19; Installation opening diameter in mm: 68-75; Warranty in years: 2; Assortment: Ecoline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC001744; Suitable for wall mounting: No; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Covering of the luminaire with thermally insulating material possible: No; Constant light output (CLO): Yes; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Exchangeable control gear: No; Emergency power supply integrated: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Colour of light adjustable: No; Luminous flux adjustable: No; Beam angle adjustable: No  
diameter: 85mm