

**DOTLUX LED floodlight HLFplus 800W 5000K 1-10V dimmable 60° beam angle**

Order number: 4872-150060

The compact HLFplus high-performance floodlight is ideal for sports fields and soccer pitches, large parking lots, construction site and crane lights and much more.

- Extremely flexible application options thanks to various beam angles (10°, 15°, 30°, 45°, 60°, 100°x38°)
- Excellent light distribution with minimal ULR values and low light scattering losses thanks to asymmetrical 100°x38° beam angle
- Safe operation outdoors thanks to powder-coated housing with high IP protection (IP66) and real glass cover
- Very high operational reliability thanks to integrated Multi Driver Technology: each spotlight has several independent power supplies with integrated 10KV overvoltage protection and a 7-year DOTLUX guarantee with an above-average service life: L80>80,000h
- Adjustable brackets for suspended, upright and wall mounting included
- Available with dimming function on request (FUNK/ZIGBEE/DMX/DALI)
- This luminaire is flicker-free and therefore also suitable for high-definition television recordings (HD)
- Sustainable product design thanks to easily replaceable components
- Other light colors can be ordered from 1pc
- No mounting accessories included

Net luminous flux in lumens: 108000; Lumen per watt: 135; Power consumption in watts: 800; Beam angle: 60; protection class (IP): IP66; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: approx. 80.000 h at 25°C; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 82; Power Factor: 0,97; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 135; Protection class: I; Voltage type: AC/DC; Housing colour: gray; Suited for emergency lighting: yes; Switch cycles: > 160.000; Overvoltage protection: up to 10000 V; Warranty in years: 7; L80/B10: 80000,1; Suitable for surface mounting: No; Suitable for mounting: No; Dimming without dimmer: No; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 80000,1; LED-Lifetime light source L70/B50 at 25°C: 160000; ETIM Gruppen-ID: EC001744; With illuminant: Yes; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: No; Lamp holder: -; Material cover: Glass transparent; Type of control gear: LED operating device current-controlled; With control gear: Yes; Dimming 0-10 V: Yes; Dimming 1-10 V: Yes; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Light distributor: Reflector; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK08; Suitable for emergency lighting: Yes; With movement sensor: No; With light sensor: No; Covering of the luminaire with thermally insulating material possible: No; Filament test according to IEC 60695-2-11: -; Connection type: Screwed terminal; Operation by Bluetooth: No; Compatible with Casambi: Yes; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Reflector: -; Suitable for low voltage cable system: No; Suitable for clamp-mounting: No; Suitable for light-track mounting: No; Suitable for pedestal/floor mounting: Yes; Suitable for traverse mounting: Yes; Exchangeable control gear: Yes; Lamp type: LED not exchangeable; Emergency power supply integrated: No; Surface brushed: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 160000; Lifetime L90/B10 at 25°C: 40000; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Light outlet: Direct; Colour of light adjustable: No; Luminous flux adjustable: No; Beam angle adjustable: No; Adjustability: Rotatable; Light sharing: Symmetric; Surface protection: Powder coating; Beam angle: Wide beam 41-80° width: 668mm