

DOTLUX LED floodlight LENSplus 200W 5000K 60°x120° beam angle

Order number: 4867-150065

Large variety of different beam angles enables optimum illumination for every situation

- Reliable operation thanks to highly efficient Lumileds® LEDs with 3-step MacAdam binning
- Solid, waterproof, ADC12 die-cast aluminum housing with pressure equalization valve (IP 66/IK08) and high-quality powder coating from Akzo Nobel
- ESG glass "ULTRA CLEAR" highly transparent glass for excellent light color and improved light output
- Durable industrial power supply units with 10kV overvoltage protection
- Curved mounting bracket enables easy installation without having to dismantle the bracket (freely rotatable 320°)
- Easy installation thanks to cable connector
- Sustainable product design thanks to easily replaceable components

Power consumption in watts: 200; Net luminous flux in lumens: 26150; Lumen per watt: 130; Beam angle: 60 x 120; protection class (IP): IP66; Light color: white; Input voltage: 176 - 240 V AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 82; Power Factor: 98; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 130; Protection class: I; Voltage type: AC/DC; Housing colour: black; Suited for emergency lighting: No; Switch cycles: > 100.000; Overvoltage protection: up to 10000 V; Warranty in years: 7; L80/B10: 50000; Suited for surface mounting: Yes; Suited for mounting: No; Dimming without dimmer: No; Assortment: Highline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 100000; ETIM Gruppen-ID: EC001744; With illuminant: Yes; Suited for wall mounting: Yes; Suited for suspended mounting: No; Suited for ceiling mounting: Yes; Suited for workplace according to EN 12464-1: No; Lamp holder: -; Material cover: Glass transparent; Type of control gear: LED operating device current-controlled; With control gear: Yes; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Light distributor: Focal lens; Colour consistency (MacAdam ellipse): SDCM5; Impact strength: IK08; Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: Yes; Suited for emergency lighting: No; With movement sensor: Yes; With light sensor: No; Covering of the luminaire with thermally insulating material possible: No; Type of wiring: Ending; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Suited for low voltage cable system: No; Suited for clamp-mounting: Yes; Suited for light-track mounting: No; Suited for pedestal/floor mounting: Yes; Suited for traverse mounting: Yes; Lamp type: LED not exchangeable; Emergency power supply integrated: No; Surface brushed: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 100000; Lifetime L90/B10 at 25°C: 25000; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Light sharing: Asymmetric; Light outlet: Direct; Colour of light adjustable: No; Luminous flux adjustable: No; Adjustability: Swivelling; Surface protection: Powder coating; Connection type: Other width: 345mm