

DOTLUX LED floodlight LENSplus 50W 5000K 30°60° beam angle

Order number: 4864-050060-B-Ware

Wide variety of different beam angles enables optimum illumination for every situation

- Reliable operation thanks to highly efficient Lumileds® LEDs with 3-step MacAdam binning
- Solid, waterproof, ADC12 die-cast aluminum housing with pressure equalization valve (IP 66/IK08) and high-quality powder coating from Akzo Nobel
- ESG "ULTRA CLEAR" highly transparent glass for excellent light color and improved light output
- Durable industrial power supply with 10kV overvoltage protection
- Curved mounting bracket allows easy mounting without disassembling the bracket (freely rotatable 320°)
- Incl. 1.5m UV-stable rubber cable (H05RN-F open ends)
- Replaceable components therefore repairable
- Sustainable product design due to easily replaceable components

Power consumption in watts: 50; Net luminous flux in lumens: 6300; Lumen per watt: 126; Beam angle: 30x60; protection class (IP): IP66; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 82; Power Factor: 0,98; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 126; Protection class: I; Housing colour: black; Suited for emergency lighting: No; Switch cycles: > 100.000; Overvoltage protection: up to 6000 V; Input voltage span: 220-240; Warranty in years: 0; L80/B10: 50000; Suitable for surface mounting: Yes; Suitable for mounting: No; Dimming without dimmer: No; Input voltage range luminaire: 220-240; Assortment: Highline; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 100000; With illuminant: Yes; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: Yes; Suitable for workplace according to EN 12464-1: No; Lamp holder: -; Material cover: Glass transparent; Type of control gear: LED operating device current-controlled; With control gear: Yes; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Light distributor: Focal lens; Colour consistency (MacAdam ellipse): SDCM6; Impact strength: IK08; Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: Yes; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: No; Constant light output (CLO): No; Type of wiring: Ending; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Suitable for low voltage cable system: No; Suitable for clamp-mounting: Yes; Suitable for light-track mounting: No; Suitable for pedestal/floor mounting: Yes; Suitable for traverse mounting: Yes; Exchangeable control gear: No; Lamp type: LED; Emergency power supply integrated: No; Surface brushed: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 100000; Lifetime L90/B10 at 25°C: 25000; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Light sharing: Asymmetric; Light outlet: Direct; Colour of light adjustable: No; Luminous flux adjustable: No; Beam angle adjustable: No; Adjustability: Swivelling; Surface protection: Powder coating; Beam angle: Extreme wide beam >80°; Connection type: Other width: 240mm