

DOTLUX LED floor lamp STYLEbutler 80W 4000K daylight dependent dimming silver

Order number: 5248-040080

- Outstanding UGR <12 VDU workstation lighting ensures fatigue-free work thanks to flicker-free light
 - Illuminate up to two workstations with one luminaire in compliance with standards thanks to optimized reflector technology
 - Stable U-steel base allows cables to be routed to the front or rear
 - IA technology with high indirect light component of 75% improves the feeling of space and creates homogeneous and shadow-free light distribution
 - Best contrast rendition with very good color rendering and constant color temperature due to 3-Step MacAdam Binning
 - Separate, infinitely variable dimming and switching of indirect and direct light via the integrated glass touch panel
 - Four different operating modes adjustable via rotary switch on luminaire head:
1. Presence sensor active (dims the luminaire to 30% brightness after 10 minutes of absence and deactivates the luminaire after a further 10 minutes)
 2. Daylight sensor/constant light function active (automatically saves the set brightness and adjusts it to the daylight level)
 3. Presence sensor Daylight sensor (both sensors active)
 4. Both sensors deactivated

Power consumption in watts: 80; Net luminous flux in lumens: 10200; Lumen per watt: 127; Beam angle: 80x140; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,94; Inrush current in A: 0; Lumen per watt: 127; Protection class: I; Voltage type: AC; Glare-free: UGR < 12; Switch cycles: > 100.000; Warranty in years: 5; L80/B10: 50000; similar to RAL-Colour: 9006; Dimming without dimmer: No; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 100000; ETIM Group Identification Number: EC000300; With illuminant: Yes; Suitable for workplace according to EN 12464-1: Yes; Suitable for number of light sources: 1; Lamp holder: -; Material cover: Plastic matt/satinized; Type of control gear: LED operating device voltage-controlled; With control gear: Yes; Dimming 0-10 V: No; Dimming 1-10 V: Yes; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): Yes; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: Yes; Dimming Zigbee: No; Dimming with push-button: No; No dim function: No; Light distributor: Reflector; Colour consistency (MacAdam ellipse): SDCM3; With movement sensor: Yes; With light sensor: Yes; Constant light output (CLO): Yes; Photobiological safety according to EN 62471: RG1; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Electrical connection with connector system: No; Luminaire heads flexible: No; Direct-/indirect proportion separately controllable: Yes; Adjustable: Nein; Exchangeable control gear: Yes; Suitable for lamp power in w: -; Lamp type: LED not exchangeable; With dimmer: Yes; With presence indicator: No; With reflector: Yes; With switch: No; With separate reading light: No; Material: Aluminium; Dimming DALI-2: No; Dimming phase cut-on: No; Lifetime L70/B50 at 25°C: 100000; Lifetime L90/B10 at 25°C: 25000; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Energy efficiency class of the light source of a luminaire: E; Colour of light adjustable: No; Beam angle adjustable: No; Type of grid: Matt; Light sharing: Symmetric; Light outlet: Direct/indirect; Luminous flux adjustable: Continuously variable; Housing colour: silver width: 50mm