

DOTLUX LED high bay floodlight COOLER 100W 5000K 120°beam angle

Order number: 5260-050120-B-Ware

- Suitable for high temperature environments up to +70°C
- Cold forged heat sink with 2 times higher thermal conductivity than die casting ensures optimal heat dissipation.
- Vertical cooling fins prevent dust buildup and provide durable cooling
- Extremely robust and durable ESG real glass cover also resists oil and cleaning agents
- Pressure equalization valve extends seal life and prevents condensation inside the fixture
- Modular design for different power spectrums
- Reduced glare UGR<19 for 60° version

Power consumption in watts: 100; Net luminous flux in lumens: 15300; Lumen per watt: 153; Beam angle: 120; protection class (IP): IP66; Input voltage: 176 - 240 V AC/DC; Service life: approx. 70.000 h at 25°C; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 153; Protection class: I; Voltage type: AC; Housing colour: black; Switch cycles: > 140.000; Overvoltage protection: up to 10000 V; Warranty in years: 0; L80/B10: 100000; Assortment: Highline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 100000; LED-Lifetime light source L70/B50 at 25°C: 147000; ETIM Gruppen-ID: ECO01744; Impact strength: IK08; Lifetime L70/B50 at 25°C: 147000; Pulse duration in µs: 0
diameter: 220mm