

**DOTLUX LED light band system LINEAcompact 50W wide beam 2886mm luminaire/blind unit 5000K not dimmable**

Order number: 4943-050160

- New light band concept with 2-length light units for fastest and easiest installation
- All units are delivered fully assembled and only need to be plugged together
- Flexible phase selection directly at the luminaire
- Patent-protected LED cover ensures error-free assembly
- High-quality aluminum core board guarantees perfect cooling and a long service life of the LM80 certified LEDs
- Future-proof with replaceable LED module and separate driver

Power consumption in watts: 50; Net luminous flux in lumens: 8500; Beam angle: 160; protection class (IP): IP54; Input voltage: 176 - 240 V AC/DC; Service life: ; Color temperature in Kelvin: 5000; Color-rendering-index: CRI > 82; Power Factor: 0,98; Inrush current in A: 0; Protection class: I; Voltage type: AC; Switch cycles: > 200.000; ETIM Group Identification Number: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in  $\mu$ s: 0  
width: 66mm