

DOTLUX LED luminaire LUNAsilver Ø490mm 36W COLORselect IP44

Order number: 3670-2FW160

- \"COLORselect\": 3 light colors in one luminaire. The right light color can be set for every application environment
1. Warm white 3,000 K: Hotel, store, wellness/spa areas, home & living
 2. Neutral white 4,000 K: Office, gastronomy, industry, sanitary, retirement homes and hospitals
 3. Daylight white 5,700 K: Industry, meeting rooms, educational institutions, office
- Frosted cover provides shadow-free light distribution
 - Stable PMMA plastic cover
 - Self-cooling LED module
 - Integrated luminaire connection with pressure clamp
 - Suitable for central battery (3372-0FW160 and 3670-0FW160 only)
 - With illuminated corona (indirect lighting)
 - Sustainable product design due to easily replaceable components

Power consumption in watts: 36; Net luminous flux in lumens: max.3500; Lumen per watt: 97; Beam angle: 160; protection class (IP): IP44; Light color: multicoloured; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,95; Inrush current in A: 0; IK protection: IK07; Lumen per watt: 97; Housing colour: multicoloured; Suited for emergency lighting: No; Switch cycles: > 100.000; Warranty in years: 5; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Material cover: Plastic, opal; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK07; Suitable for emergency lighting: No; Covering of the luminaire with thermally insulating material possible: No; Colour of light adjustable: Positions; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: F
diameter: 490mm