

DOTLUX LED luminaire LUNAsilver Ø490mm 36W COLORselect IP44

Order number: 3670-399160-B-Ware

1. Decorative ring made of high quality brushed aluminum
2. Cozy atmosphere due to indirect light components
3. Shadow-free light distribution with very stable PMMA cover IK07
4. Constant light output due to large-area aluminum core board
5. Easy installation, thanks to through-wireable luminaire terminal block
6. Sustainable, repairable product design

Power consumption in watts: 36; Net luminous flux in lumens: max.3500; Lumen per watt: 97; Beam angle: 120; protection class (IP): IP44; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,96; Inrush current in A: 0; IK protection: IK07; Lumen per watt: 97; Suited for emergency lighting: No; Switch cycles: > 100.000; Warranty in years: 0; Assortment: Proline; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK07; Suitable for emergency lighting: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany
diameter: 490mm