

DOTLUX LED luminaire LUNAsilver-sensor Ø490mm 36W COLORselect IP44

Order number: 4833-0FW160-B-Ware

- Decorative ring made of high-quality brushed aluminum
- Comfortable atmosphere due to indirect light components
- Silent sensor function
- On/Off function to 100% light intensity via daylight sensor, then 0% light intensity
- Shadow-free light distribution with very stable PMMA cover IK07
- Constant light output due to large area aluminum core board
- Easy installation, thanks to through-wireable luminaire terminal block
- Sustainable, repairable product design

Net luminous flux in lumens: max.3200; Lumen per watt: 89; Power consumption in watts: 36; Beam angle: 120; protection class (IP): IP44; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,9; IK protection: IK07; Lumen per watt: 89; Suited for emergency lighting: No; Switch cycles: > 100.000; Warranty in years: 0; Assortment: Proline; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK07; Suitable for emergency lighting: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No
diameter: 490mm