

DOTLUX LED module QUICK-FIXdc 1130mm max.22W 500mA (40-45V DC) 5700K Set 50 pieces

Order number: 5832-50

- Universal magnetic LED light module for the professional replacement of T5 & T8 fluorescent tubes
- Highly efficient 160 Watt LED board with lowest current consumption enables a system efficiency of up to 191 Lm/Watt
- Glare-free polycarbonate cover with 120° beam angle
- Tool-free replacement of the LED module even by a non-specialist thanks to DC system plug
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- 3 magnets and 60cm long connection cable included in the scope of delivery

The properties of the power supply unit also influence the properties of the luminaire system, e.g. dimmable, suitable for central battery, flicker-free, etc.

Recommended ballast not dimmable 100,000 hours Article number: 5136

Power consumption of the module with different operating currents:

- 22W@ 500mA = 3800lm = 173lm/W
- 15W@ 350mA = 2775lm = 185lm/W
- 10.5W@ 250mA = 2000lm = 190lm/W
- 6.3W@ 150mA = 1205lm = 191lm/W

Lumen per watt: max. 191; Power consumption in watts: 6,3/10.5/15/22; Net luminous flux in lumens: 1205/2000/2775/3800; Beam angle: 120; protection class (IP): IP20; Service life: approx. 200,000 h at 25°C; Color temperature in Kelvin: 5700; Power Factor: 0,9; Lumen per watt: max. 191; Protection class: II; Voltage type: DC; Input voltage span: 40-45; Warranty in years: 5; L80/B10: 100000; Dimming without dimmer: No; ENABLED licensed product: Yes; Input voltage range luminaire: 40-45; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: B; Lifetime L80/B10 at 25°C: 100000; ETIM Gruppen-ID: EC000996; No dim function: No; Colour consistency (McAdam ellipse): SDCM6; Connection type: Cable; Photobiological safety according to EN 62471: RG1; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Flexible: Nein; Suitable for traffic lights: No; External driver required: Yes; Suitable for constant voltage: No; Suitable for general lighting: Yes; Suitable for constant current: Yes; Suitable for rail traffic: No; Suitable for matrix information boards: No; Suitable for variable road signs: No; Light colour according to EN 12464-1: daylight white >5300 K; BEG funding: Only relevant in Germany; LED-Betriebsstrom in mA: 150/250/350/500; Shape: Rectangular; Colour: White
width: 20mm