

DOTLUX LED moisture-proof luminaire MISTRAL IP66 1540mm 27W 4000K frosted B-goods

Order number: 2356-540120-B-Ware

- Faster installation thanks to innovative luminaire design. Combination of LED gear tray and cover.
 - Individually replaceable branded components for the lowest maintenance costs
 - UV-stable, shatterproof IK08/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
 - 5-pole through-wired with two internal luminaire connection terminals
 - Stainless steel catches with integrated anti-theft device
 - Mounting accessories supplied (chain/ceiling/wall mounting) incl. rear panel punchings
-
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in locations with a fire hazard (DIN EN 60598-2-24, VDE 0711-2-24) This LED luminaire is suitable for use in food processing plants.
 - This means it can also be used in areas that are certified in accordance with the International Featured Standard (IFS) or British Retail Consortium (BRC).
 - Sustainable product design thanks to easily replaceable components

Lumen per watt: 143; Power consumption in watts: 27; Net luminous flux in lumens: 3860; Beam angle: 120; protection class (IP): IP66; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,9; IK protection: IK08; Lumen per watt: 143; Protection class: I; Housing colour: gray; Switch cycles: > 100.000; Food-Ready: Yes; Warranty in years: 0; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Group Identification Number: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK08; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No