

DOTLUX LED moisture-proof luminaire MISTRAL IP66 640mm 26W 4000K frosted

Order number: 2354-340120-B-Ware

- Faster installation due to new type of luminaire design. Combination of LED gear tray and cover.
- Individually replaceable branded components for lowest maintenance costs.
- UV-stable, shatterproof IK08/IP66 polycarbonate housing with frosted cover provides shadow-free light distribution
- 5-pole through-wired with two internal luminaire terminals
- 2 full cable glands & blanking plugs
- Stainless steel latches with integrated anti-theft device
- Mounting accessories included (chain/ceiling/wall mounting) incl. back panel punching
- The D-mark of this luminaire with limited surface temperature is a basic requirement for luminaires in fire hazardous locations (DIN EN 60598-2-24, VDE 0711-2-24)
- This LED luminaire is suitable for use in food processing plants.
- Therefore it can also be used in areas which are certified according to the International Featured Standard (IFS) or British Retail Consortium (BRC).

Power consumption in watts: 26; Net luminous flux in lumens: 3500; Lumen per watt: 135; Beam angle: 120; protection class (IP): IP66; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 135; Protection class: I; Housing colour: gray; Switch cycles: > 100.000; Food-Ready: Yes; Warranty in years: 0; Assortment: Proline; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK08; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0
width: 100mm