

DOTLUX LED office lamp OFFICE 1200x300mm 54W COLORselect dimmable 1-10V UGR<19 (incl. suspension)

Order number: 3304-0FW120

- SEAMLESS CONNECT allows easy and quick installation of multiple luminaires.
- Integrated 3-step dimming function via the light switch without separate dimmer!
 - 100% - Switch on light
 - 50% - light off/on
 - 10% - light on/off/switch on
- Integrated driver saves the installation of a power connection box (incl. canopy)
- Glare-free, homogeneous and shadow-free light distribution due to 3-layer glass diffuser
- Better contrast rendition with very good color rendition and constant color temperature (3-Step MacAdam Binning)
- High-quality SAMSUNG® LEDs
- The flicker-free light rendering ensures optimum vision, is easy on the eyes for fatigue-free working and creates a pleasant atmosphere in offices, conference rooms and hotels.

Power consumption in watts: 54; Net luminous flux in lumens: 5670; Lumen per watt: 105; Beam angle: 120; protection class (IP): IP40; Light color: multicoloured; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5500; Color-rendering-index: CRI > 82; Power Factor: 0,97; Inrush current in A: 0; IK protection: IK03; Lumen per watt: 105; Protection class: II; Voltage type: AC; Housing colour: white; Suited for emergency lighting: yes; Glare-free: UGR < 19; Switch cycles: > 100.000; Overvoltage protection: up to 4000 V; Warranty in years: 5; Rope length: 1500; Dimming without dimmer: yes; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: E0001743; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: Yes; Dimming LineSwitch: Yes; No dim function: No; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK03; Suitable for emergency lighting: Yes; Colour of light adjustable: Positions; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: E
width: 300mm