

DOTLUX LED panel FLATeco 595x595 max. 40W 4000K UGR<19

Order number: 3665-240120

- LED recessed luminaire with microprismatic cover CDP Nano
- Excellent price-performance ratio
- Glare-free, homogeneous and shadow-free light distribution
- Fatigue-free working due to flicker-free light
- Better contrast rendition with very good color rendition and constant color temperature
- White frame and connection cable with connector
- LM80 certified LEDs

Power levels:

40W @ 1050 mA

36W @ 950 mA

27W @ 700 mA

20W @ 500 mA

14W @ 350 mA

Power consumption in watts: max. 40; Net luminous flux in lumens: max. 4000; Lumen per watt: 100; Beam angle: 120; protection class (IP): IP20; Light color: white; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Inrush current in A: 0; IK protection: ; Lumen per watt: 100; Protection class: III; Housing colour: white; Glare-free: UGR < 19; Switch cycles: > 100.000; Warranty in years: 3; Assortment: Ecoline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Material cover: Plastic matt/satinized; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK02; Covering of the luminaire with thermally insulating material possible: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Colour of light adjustable: No
width: 595mm