

DOTLUX LED panel FLATevo 620x620 UGR19 4000K 37W Set of 4 incl. power supply unit

Order number: 5499

- All-in-one solution. Get started right away, the set comes directly with panels and matching power supply units.
- Includes 4x panel and 4x 950mA power supply unit
- LED recessed luminaire with CDP Nano microprismatic cover for glare-free light distribution
- UGR<19 suitable for VDU workstations
- Low-current LEDs combined with large-area rear cooling guarantee a long LED service life and consequently low maintenance costs
- 37W @ 950 mA = 4550Lm

Net luminous flux in lumens: 4550; Lumen per watt: 123; Power consumption in watts: 37; Beam angle: 90; protection class (IP): IP20; Light color: white; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; IK protection: ; Lumen per watt: 123; Protection class: III; Voltage type: AC; Housing colour: white; Suited for emergency lighting: No; Glare-free: UGR < 19; Input voltage span: 220-240; Warranty in years: 5; L80/B10: 50000; Suitable for mounting: Yes; Input voltage range luminaire: 220-240; Energy efficiency class according to EU regulation 2019/2015: not required; Mounting location: Indoor; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 82000; ETIM Gruppen-ID: EC002892; Material cover: Plastic matt/satinized; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK02; Suitable for emergency lighting: No; Covering of the luminaire with thermally insulating material possible: No; Lifetime L70/B50 at 25°C: 82000; Lifetime L90/B10 at 25°C: 20500; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Colour of light adjustable: No
width: 620mm