

**DOTLUX LED panel FLATtwice 1200x300mm 40W UGR<19 4000K DALI dimmable**

Order number: 5199-040110

- Ultra flat pendant luminaire with sturdy, elegant profile housing
- Stylish appearance thanks to screwless design and elegant Y-rope suspension
- Quick installation thanks to magnetic ceiling box
- Direct and indirect light distribution in the ratio 70% DOWN / 30% UP
- Glare-free, homogeneous and shadow-free light distribution / smooth top UGR<19

Power consumption in watts: 40; Net luminous flux in lumens: 4200; Lumen per watt: 105; Beam angle: 110; protection class (IP): IP20; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; Lumen per watt: 105; Protection class: I; Housing colour: white; Glare-free: UGR < 19; Switch cycles: > 100.000; similar to RAL-Colour: 9003; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO02892; Material cover: Plastic matt/satinized; Dimming with push-button: Yes; No dim function: No; Colour consistency (McAdam ellipse): SDCM6; Covering of the luminaire with thermally insulating material possible: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Dimming DALI-2: Yes; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: E; Colour of light adjustable: No  
width: 300mm