

DOTLUX LED panel FLATtwice 1200x300mm 40W UGR<19 4000K not dimmable

Order number: 5198-040110

- Ultra flat pendant luminaire with sturdy, elegant profile housing
- Stylish appearance thanks to screwless design and elegant Y-rope suspension
- Quick installation thanks to magnetic ceiling box
- Direct and indirect light distribution in the ratio 70% DOWN / 30% UP
- Glare-free, homogeneous and shadow-free light distribution / smooth top UGR<19

Power consumption in watts: 40; Net luminous flux in lumens: 4200; Lumen per watt: 105; Beam angle: 110; protection class (IP): IP20; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; Lumen per watt: 105; Protection class: I; Housing colour: white; Glare-free: UGR < 19; Switch cycles: > 100.000; similar to RAL-Colour: 9003; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Covering of the luminaire with thermally insulating material possible: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: E; Colour of light adjustable: No width: 300mm