

**DOTLUX LED panel RIMLESS 620x620x max.42W 1050mA 4000K**

Order number: 5363-040120-B-Ware

- Save even more energy with highly efficient LEDs with a luminous efficacy of 165Lm/W
- Frameless design for large-area illumination (also great for SKYLIGHT motifs)
- Homogeneous luminous surface with frosted cover provides pleasant light distribution
- Easy to install and service thanks to DC system plug (Plug&Play compatible with all DOTLUX power supplies)

Power consumption with through-wired power supply Art. 5334

45W @1050 mA = 6950Lm

42W @ 950 mA = 6490Lm

30W @ 700 mA = 4800Lm

26W @ 600 mA = 4120Lm

This product is compatible with our surface mount frame 5226.

Power consumption in watts: max. 42; Net luminous flux in lumens: max. 6950; Lumen per watt: max.178; Beam angle: 120; protection class (IP): IP40; Light color: white; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 82; Inrush current in A: 0; Lumen per watt: max.178; Protection class: III; Input voltage span: 37-40; Warranty in years: 0; Input voltage range luminaire: 37-40; Assortment: Proline; Colour consistency (McAdam ellipse): SDCM6; Pulse duration in µs: 0; BEG funding: only relevant in Germany; Colour of light adjustable: No  
width: 620mm