

DOTLUX LED recessed panel SQUAREeco IP20 16W 3000K 175x175mm Set 5 pieces

Order number: 600097

- Flat design with integrated power supply unit enables use even in difficult installation locations
- Backlight technology with robust aluminum core board and good thermal management
- Wide housing rebate covers inaccurately cut installation opening
- Plastic-coated metal clips ensure a secure hold
- Set of 5

Net luminous flux in lumens: 1280; Power consumption in watts: 16; Lumen per watt: 80; Beam angle: 120; protection class (IP): IP20; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 20.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Power Factor: 0,7; Lumen per watt: 80; Protection class: II; Voltage type: AC; Housing colour: white; Switch cycles: > 40.000; Installation opening width in mm: 150; Installation opening diameter in mm: 140-150; Installation opening length in mm: 150; Warranty in years: 2; Assortment: Ecoline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: ECO01744; Material cover: Plastic, opal; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Covering of the luminaire with thermally insulating material possible: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Colour of light adjustable: No
width: 175mm