

**DOTLUX LED refurbishment light QUICK-FIX24V 500x15mm 7.5W 3000K PU12**

Order number: 5186-130120

- Universal luminaire-in-luminaire system (24V constant voltage) for quick and easy replacement of almost all light sources in existing ceiling and wall luminaires
  - Simple wiring with full flexibility thanks to integrated constant current drivers. The luminaire only needs to be supplied with 24V DC.
  - 2 pre-installed neodymium magnets hold the light securely in place
  - Through-wired spring pressure connection terminals at both ends
  - Dimmable via our 24V PWM power supply units, e.g. also DALI
  - 12 LED lights incl. 20 matching connectors
  - Up to 6 lights per 10W can be operated in series connection
- 
- Can be cut to length individually every 10cm (2 mounting holes and additional soldering surfaces per 10cm)
  - In addition, 10 mounting holes are available per 50cm luminaire for alternative fastening
  - Cable can be used for single-wire wiring (rigid conductor 0.5-0.75mm<sup>2</sup>)
  - Incl. release tool for releasing an already plugged-in cable at the plug-in terminal connection
  - ESD contact protection up to 8kV for the complete luminaire
  - Can only be ordered in packaging units, not available individually
  - 1 PU contains 12 pieces

Power consumption in watts: 7,5; Net luminous flux in lumens: 1390; Lumen per watt: 185; Beam angle: 120; protection class (IP): IP20; Color temperature in Kelvin: 3000; Power Factor: 1; Severable by mm: 100; Tc temperature in °C: 85; Lumen per watt: 185; Voltage type: DC; Switch cycles: > 60.000; Input voltage span: 22-29; Warranty in years: 3; L80/B10: 50000; Dimming without dimmer: No; ENABLED licensed product: Yes; Input voltage range luminaire: 22-29; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: B; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 100000; ETIM Group Identification Number: EC000996; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM3; Connection type: Push-in clamp; Photobiological safety according to EN 62471: RG0; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Flexible: Nein; Suitable for traffic lights: No; External driver required: Yes; Suitable for constant voltage: Yes; Suitable for general lighting: Yes; Suitable for constant current: No; Suitable for rail traffic: No; Suitable for matrix information boards: No; Suitable for variable road signs: No; Lifetime L70/B50 at 25°C: 100000; Lifetime L90/B10 at 25°C: 25000; Light colour according to EN 12464-1: warm white <3300 K; BEG funding: only relevant in Germany; LED operating current in mA: 325; Shape: Other; Colour: White  
width: 15mm