

**DOTLUX LED rescue light EXITflip with CINEMA MODE max.2,5W 6000K incl. 6 pictograms 3h operation, Li-ion battery with self-test**

Order number: 5508-060360

- \"ONE FOR ALL\" One order number for all arrow directions
- Replaceable Li-ion battery guarantees a lighting time of 3 hours
- Various switching programs selectable: continuous or standby mode
- Wall/ceiling mounting with infinitely variable folding pictogram
- With the matching track adapter 5519, the EXITflip can be mounted in all 3-phase tracks
- Automatic self-test function with integrated operating status indicator LED
- Power consumption in standby mode less than 0.5 watts
- Power consumption in cinema mode less than 1 watt
- Power consumption in continuous operation less than 2.5 watts
- Includes 6 standard pictograms arrow (left, right, up, down)

Power consumption in watts: 2,5; Lumen per watt: 7; Net luminous flux in lumens: 18; protection class (IP): IP20; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Range of sensor: 30; Color temperature in Kelvin: 6000; Color-rendering-index: CRI > 82; Power Factor: 0,3; Lumen per watt: 7; Protection class: II; Housing colour: white; Suited for emergency lighting: yes; L80/B10: 50000; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; ETIM Gruppen-ID: EC001957; Suitable for emergency lighting: Yes; Lamp type: LED; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Material cover: Other  
width: 43mm