

DOTLUX LED rescue light EXITmulti, 2W 6000K incl.6 pictograms 3h operation. Li-FEPO4 autom. self test

Order number: 3177-160120

- \"ONE FOR ALL\" One order number for all arrow directions
- Universally mountable escape sign luminaire (2x wall, ceiling installation, rope suspension)
- Replaceable LiFePO4 battery guarantees a light duration of 3 hours
- Different switching programs selectable: continuous or stand-by mode
- Power consumption in standby mode less than 0.5 Watt
- Automatic self-test function with integrated operating status control LED
- Including 6 standard pictograms (left, right, up, down)

Power consumption in watts: 2; Net luminous flux in lumens: AC 45 / Akku 23; Lumen per watt: 22,5; protection class (IP): IP20; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Range of sensor: 30; Color temperature in Kelvin: 6000-7000; Color-rendering-index: CRI > 70; Power Factor: 0,3; IK protection: IK08; Lumen per watt: 22.5; Protection class: I; Voltage type: AC/DC; Housing colour: white; Pictogram included: Yes; Warranty in years: 3; L80/B10: 50000; Self-test: Automatic self-test; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 100000; ETIM Gruppen-ID: EC001957; With illuminant: Yes; Impact strength: IK08; Mounting method: Wall/ceiling-mounted; Lifetime L70/B50 at 25°C: 100000; Lifetime L90/B10 at 25°C: 25000; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: -; Material cover: Other
width: 40mm