

DOTLUX LED stair light EASYSTAIR 1,5 W 3000K black

Order number: 5415-130080

Query geblockt

Power consumption in watts: 1,5; Net luminous flux in lumens: 70; Lumen per watt: 47; Beam angle: 75; protection class (IP): IP44; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 40.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 92; Power Factor: 0,47; Inrush current in A: 0; IK protection: IK04; Lumen per watt: 47; Protection class: II; Voltage type: AC; Housing colour: black; Suited for emergency lighting: No; Installation opening width in mm: 53; Installation opening diameter in mm: 53; Installation opening length in mm: 53; Warranty in years: 5; L80/B10: 40000; Rated current: 0; Suitable for surface mounting: No; Suitable for mounting: Yes; ENABLED licensed product: Yes; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Mounting location: Indoor; Lifetime L80/B10 at 25°C: 40000; ETIM Gruppen-ID: EC002892; With illuminant: Yes; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: No; Suitable for light line configuration: Yes; Suitable for workplace according to EN 12464-1: Yes; Lamp holder: -; Material cover: Plastic matt/satinized; Type of grid: -; Type of control gear: LED operating device current-controlled; With control gear: No; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Light distributor: Diffuser lens/optic/panel; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK04; Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: No; Suitable for emergency lighting: No; With movement sensor: No; With air slots: No; Filament test according to IEC 60695-2-11: 650 °C - 30 s; Constant light output (CLO): Yes; Type of wiring: Ending; Connection type: Cable; Photobiological safety according to EN 62471: RG1; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Exchangeable control gear: No; Suitable for lamp power in w: 1.5; Lamp type: Compact fluorescent lamp; Emergency power supply integrated: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Colour of light adjustable: No; Beam angle adjustable: No; Surface protection housing: Lacquered; Light outlet: Direct/indirect; Luminous flux adjustable: Continuously variable; Light sharing: Symmetric/asymmetric; Beam angle: Wide beam 41-80°; Degree of protection (NEMA): 4x width: 82mm