

## DOTLUX LED street lamp RETROFITprotect E27 28W 4500K

Order number: 1666-145360

- Overvoltage protection up to 4,000 V
- No early failures: SecureSolderConnect technology prevents hairline cracks and cold solder joints
- Unique: Integrated, temperature-dependent power regulation to 50% to protect against overheating
- AirFin-Cooling: 2.5 times larger cooling surface than comparable products and up to 20% reduced weight at lamp base
- Easy replacement with Retro-Fit E27 base for common HQL/NAV lamps
- Optimally arranged LEDs enable uniform light distribution
- Lamp can be operated without conversion on HQL Voschlat devices and also directly on 230V. NAV ballasts must be disconnected.
- Lamp efficiency of up to 160 lm / W due to the use of high-quality Lm80 certified LEDs

Power consumption in watts: 28; Consumption (kWh/1000h): 28; Net luminous flux in lumens: 4480; Lumen per watt: 160; Beam angle: 360; protection class (IP): IP40; Input voltage: 100 - 240 V AC; Service life: approx. 35.000 h at 25°C; Base: E27; Color temperature in Kelvin: 4500; Color-rendering-index: CRI > 82; Power Factor: 0,91; Inrush current in A: 45; Lumen per watt: 160; Housing colour: white; Suited for emergency lighting: yes; Switch cycles: > 70.000; Warranty in years: 5; Suited for emergency power: -; ENEC-certified: ENEC 25; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: D; ETIM Gruppen-ID: EC001959; Colour consistency (McAdam ellipse): SDCM6; Suitable for emergency lighting: Yes; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Lifetime L90/B10 at 25°C: 12500; Pulse duration in µs: 50; Light colour according to EN 12464-1: neutral white 3300 to 5300 K; Lifetime L90/B50 at 25°C: 0; BEG funding: Only relevant in Germany; Colour: White diameter: 90mm