

**DOTLUX LED street light BELUGAmicro 38W 4000K without pole adapter**

Order number: 3456-B-Ware

Protection class I with integrated overvoltage protection (10,000 V)

Variety of adapters enables mounting on all pole diameters

The multilayer lens optics with CREE® LEDs enable uniform light distribution

Solid cast aluminum housing in RAL 7022 with impact resistance class IK09

Reliable and highly efficient LED driver with a service life of > 80,000h ensures low maintenance costs

Power consumption in watts: 38; Net luminous flux in lumens: 3880; Beam angle: 135°/50°; protection class (IP): IP66; Input voltage: 176 - 240 V AC/DC; Service life: approx. 80.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 75; Mast support: depending on adapter; IK protection: IK09; Protection class: I; Switch cycles: > 160.000; Overvoltage protection: up to 10000 V; Input voltage span: 127-305 V AC; Warranty in years: 0; Input voltage range luminaire: 127-305 V AC; ETIM Gruppen-ID: EC000062; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; No dim function: Yes; Impact strength: IK09; Dimming phase cut-on: No; Dimming GPRS: No; width: 190mm