

DOTLUX LED strip 48W 10mm 4000K IP66 5m roll incl. 50cm connection cable on both sides

Order number: 3943-040IP665M

- Cozy and natural light due to extra high color rendering RA>92
- Consistent color temperature due to 3-Step Mac Adam binning and specially extruded IP66 protective cover
- Very densely arranged LEDs allow homogeneous illuminated areas at smallest distances
- Secure Solder Connect Technology prevents hairline cracks and cold solder joints
- Reinforced conductive traces ensure uniform brightness
- Original 3M adhesive tape provides strong hold
- 15 cm connection cable pre-mounted on one side

Power consumption in watts: 48; Net luminous flux in lumens: 4150; Beam angle: 120; protection class (IP): IP66; Light color: white; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Color-rendering-index: CRI > 92; Amount of LED/m: 140; Severable by mm: 50; Tc temperature in °C: 67; Output W/m: 9,6; Light flux lm/m: 800; Smallest bend radius in mm: 25; Input voltage span: 24 V DC; Warranty in years: 7; Input voltage range luminaire: 24 V DC; Energy efficiency class according to EU regulation 2019/2015: F; ETIM Group Identification Number: ECO02706; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; BEG funding: Only relevant in Germany; Energy efficiency class of the light source of a luminaire: -; Colour of light adjustable: No
width: 10mm