

DOTLUX LED surface-mounted light SURFACE Ø400x62 max.26W 3000/4000/5700K COLORselect white with POWERselect

Order number: 4371-299120

- Quick and easy installation with EASYbase base plate and twistlock fastener
- Wide range of products enables use in all projects (e.g. sensor, exit, DALI ...)
- Sustainable product design thanks to easily replaceable LED module and power supply unit
- Rear and side cable entry with large cable storage space enables flexible use on site
- Ideal for residential projects thanks to impact-resistant IK10 polycarbonate housing
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor areas
- Individual light color adjustable via COLORselect (light color: 3,000 K / 4,000 K / 5,700 K)
- Adjustable light output with Powerselect (13/16/22/26W)
- Suitable for central battery

Net luminous flux in lumens: 3380/2860/2080/1690 - 4000K; Lumen per watt: 123/130/127; Power consumption in watts: 13/16/22/26; Beam angle: 120; protection class (IP): IP54; Light color: multicoloured; Input voltage: 186 - 240 AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,97; IK protection: IK10; Lumen per watt: 123/130/127; Protection class: II; Voltage type: AC; Housing colour: white; Suited for emergency lighting: yes; Installation opening width in mm: 0; Installation opening diameter in mm: 0; Installation opening length in mm: 0; Warranty in years: 5; L80/B10: 50000; Suitable for surface mounting: Yes; Suitable for mounting: No; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; ETIM Gruppen-ID: E0002892; With illuminant: Yes; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: Yes; Suitable for light line configuration: No; Surface protection housing: -; Material cover: Plastic, structured; Type of control gear: -; With control gear: Yes; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Light sharing: -; Light outlet: -; Impact strength: IK10; Suitable for emergency lighting: Yes; With movement sensor: No; With light sensor: No; Covering of the luminaire with thermally insulating material possible: No; With air slots: Yes; Type of wiring: -; Connection type: Plug connection; Colour of light adjustable: Positions; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Suitable for lamp power in w: 26; Lamp type: LED; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; BEG funding: only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: D; Beam angle adjustable: No; Luminous flux adjustable: Continuously variable; Type of grid: Other; Light distributor: Other; Beam angle: Extreme wide beam >80°; Photobiological safety according to EN 62471: Other

diameter: 400mm