

**DOTLUX LED surface mounted luminaire SURFACEsensor-exit Ø300x62 25W 3000/4000/5700K COLORselect white**

Order number: 4932-0FW120-B-Ware

- Additional 3h emergency light function with built-in lithium ion battery.
- Version with motion (radar) and daylight sensor (several luminaires can be programmed with one remote control, please order remote control separately)
- Quick and easy installation with EASYbase base plate and twistlock fastener
- Large product variety enables use in all projects ( e.g. sensor, Exit, DALI ...)
- Sustainable design, LED module, power supply unit and battery can be replaced without tools
- Rear and side cable entry with large cable storage space allow flexible use on site
- Ideal for residential projects due to impact-resistant polycarbonate housing IK10
- Modern, clear design with indirect light component
- Splash-proof housing for outdoor, wet room and indoor use
- Individual light colour adjustable with COLORselect (light colour: 3,000 K / 4,000 K / 5,700 K)
- The large luminous surface made of polycarbonate creates a uniform and at the same time ceiling-brightening light Distribution
- Flexible cable entry possible at the rear and side

Power consumption in watts: 25; Net luminous flux in lumens: 2370-2600; Beam angle: 120; protection class (IP): IP54; Light color: multicoloured; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Output Lumen during emergency: 200; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,9; IK protection: IK10; Battery runtime: 3h; Protection class: II; Voltage type: AC; Housing colour: white; Suited for emergency lighting: yes; Warranty in years: 0; Power emergency operation in W: 3; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Impact strength: IK10; Suitable for emergency lighting: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No  
diameter: 300mm