

DOTLUX LINEAplus LED trunking system 1500mm through-wired blind unit

Order number: 1987-3

- Quick-release fasteners for all connections
- Tool-free mounting rail with integrated through-wiring
- Luminaire insert with flexible phase selection (for non-dimmable version)
- Optimized transmittance of the lens
- Perfect cooling of the LED module thanks to aluminum core board
- High luminous efficacy thanks to optimized profile design
- Easily replaceable light unit
- Long service life thanks to oversized cooling
- Future-proof with replaceable LED module and separate driver
- Suitable for central battery (only DALI article no. 2811-3)

protection class (IP): IP40; Light color: -; Color temperature in Kelvin: -; Inrush current in A: 0; Housing colour: white; Warranty in years: 7; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Group Identification Number: EC002892; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Covering of the luminaire with thermally insulating material possible: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in μ s: 0; BEG funding: Only relevant in Germany; Energy efficiency class of the light source of a luminaire: -; Colour of light adjustable: No
width: 108mm