

**DOTLUX Mirror light TRENDosocket 10W 3000/4000/5700K COLORselect B-Goods**

Order number: 5321-099140-B-Ware

- Modern, stylish design with integrated Schuko socket outlet and side switch
- Maximum lighting surface without visible screw connections
- EASYbase platform enables quick and easy installation
- Installation on existing drill holes possible thanks to free surface on the base plate
- 2 cable inlets pre-installed (individual inlets can be drilled into the aluminum base if required)
- Simply set your desired light color yourself, one article number - three light colors through COLORselect
- Sustainable product design thanks to easily replaceable components

Power consumption in watts: 10; Net luminous flux in lumens: 1050; Lumen per watt: 105; Beam angle: 140; protection class (IP): IP44; Light color: multicoloured; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 105; Protection class: I; Housing colour: multicoloured; Switch cycles: > 100.000; Input voltage span: 220-240; Warranty in years: 0; similar to RAL-Colour: 9006; Input voltage range luminaire: 220-240; Assortment: Proline; ETIM Gruppen-ID: EC002892; Material cover: Plastic matt/satinized; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK08; Colour of light adjustable: Positions; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany  
width: 85mm