

DOTLUX Netzteil 150W 48V 3,13A CV+CC

Order number: 4323

the power supply supports constant current and constant voltage output in dual mode.

Thanks to the 91% high efficiency and fanless design, the series can operate under free air convection in the temperature range of -40°C to +90°C. IP65 protection class due to intelligent design and aluminum housing.

Power consumption in watts: 105; protection class (IP): IP65; Frequency range in Hz: 47-63; Output current in A: 3,13; Power Factor: 0,97; Inrush current in A: 0; Protection class: I; Output voltage: 48 DC; Input voltage span: 100-305 AC / 142-431 DC; Warranty in years: 3; Input voltage range luminaire: 100-305 AC / 142-431 DC; Energy efficiency class according to EU regulation 2019/2015: not required; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in μ s: 0 width: 63mm