

**DOTLUX QUICK-FIXplus 8W 4000K replaceable LED module**

Order number: 3377-140170

- Universal MAGNET LED module with integrated driver for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Extra high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 150lm/W thanks to low-current LEDs and therefore long service life
- Our QUICK-FIXplus have DIN EN60598-2-22:2014 certification, which confirms approval in the field of emergency lighting.
- Special lenses with 170° beam angle ensure absolutely shadow-free light distribution even in larger luminaires up to 500 mm
- Suitable for central battery
- Tool-free replacement of the LED module even by a non-specialist thanks to AC system plug

Lumen per watt: 150; Power consumption in watts: 8; Net luminous flux in lumens: 1200; Beam angle: 170; protection class (IP): IP20; Input voltage: 186 - 240 AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 4000; Lumen per watt: 150; Protection class: II; Voltage type: AC/DC; Switch cycles: > 100.000; Warranty in years: 3; Dimming without dimmer: No; ENABLED licensed product: Yes; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: E; Mounting location: Indoor; ETIM Group Identification Number: EC000996; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM4; Connection type: Cable; Photobiological safety according to EN 62471: RG1; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Flexible: Nein; Suitable for traffic lights: No; External driver required: No; Suitable for constant voltage: No; Suitable for general lighting: Yes; Suitable for constant current: Yes; Suitable for rail traffic: No; Suitable for matrix information boards: No; Suitable for variable road signs: No; Light colour according to EN 12464-1: neutral white 3300 to 5300 K; BEG funding: only relevant in Germany; LED operating current in mA: 45; Shape: Round; Colour: White diameter: 120mm