

DOTLUX Refurbishment light QUICK-FIXadapt 29W 3000K

Order number: 6161-030170

- Universal luminaire-in-luminaire system for quick and easy replacement of all conventional light sources in ceiling and wall luminaires
- Tool-free replacement of the QUICK-FIXadapter even by a non-specialist thanks to DC system plug
- Special lenses with 170° beam angle
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- with the matching 5068-1 power supply unit, the QUICK-FIX-adapt can be set up to 700mA.
- Inner diameter 25cm
- outer diameter 30cm
- can be combined with emergency power battery kit art. no. 5315 corresponds to an emergency light output of 1.5 watts at 3H

Power consumption and net luminous flux of the luminaire with different operating currents:

- 12W@ 300mA = 2000lm = 167lm/W
- 14W@ 350mA = 2320lm = 166lm/W
- 16W@ 400mA = 2640lm = 165lm/W
- 18W@ 450mA = 2970lm = 165lm/W
- 23W@ 550mA = 3580lm = 156lm/W
- 25W@ 600mA = 3840lm = 154lm/W
- 27W@ 650mA = 4130lm = 153lm/W
- 29W@ 700mA = 4360lm = 150lm/W

Power consumption in watts: 29; Net luminous flux in lumens: 4360; Lumen per watt: 150; Beam angle: 170; protection class (IP): IP20; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Power Factor: 0,9; Lumen per watt: 150; Protection class: -; Voltage type: DC; Switch cycles: > 100.000; Input voltage span: 40-43; Warranty in years: 3; L80/B10: 50000; Dimming without dimmer: No; ENABLED licensed product: Yes; Input voltage range luminaire: 40-43; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: D; Lifetime L80/B10 at 25°C: 50000; ETIM Group Identification Number: EC000996; Colour consistency (McAdam ellipse): SDCM1; Connection type: Cable; Photobiological safety according to EN 62471: RG1; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Flexible: Nein; Suitable for traffic lights: No; External driver required: Yes; Suitable for constant voltage: No; Suitable for general lighting: Yes; Suitable for constant current: Yes; Suitable for rail traffic: No; Suitable for matrix information boards: No; Suitable for variable road signs: No; Light colour according to EN 12464-1: -; BEG funding: Only relevant in Germany; LED operating current in mA: 700; Shape: Round; Colour: Yellow diameter: 300mm