

**DOTLUX Wall light BRICK 10W COLORselect black**

Order number: 5296-098060

- Particularly soft lighting effect thanks to internal reflector creates a great atmosphere
- Robust, splash-proof housing made of aluminum and real glass offers the best protection for outdoor use with IP65
- Phase-cut dimmable and therefore also suitable for indoor use as a modern wall light
- Through-wiring possible thanks to two large cable inlet rubbers and quick-connect terminal
- EasyBase platform enables quick and easy installation
- Vertical mounting also possible
- Housing color similar to RAL 9005

Net luminous flux in lumens: 750; Lumen per watt: 75; Power consumption in watts: 10; Beam angle: 60x115x40; protection class (IP): IP65; Light color: multicoloured; Input voltage: 186 - 240 AC/DC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/3500/4000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; IK protection: IK03; Lumen per watt: 75; Protection class: I; Voltage type: AC/DC; Housing colour: black; Suited for emergency lighting: No; Switch cycles: > 100.000; Installation opening diameter in mm: 0; Warranty in years: 3; L80/B10: 50000; similar to RAL-Colour: 9005; Suitable for surface mounting: Yes; Suitable for mounting: No; Energy efficiency class according to EU regulation 2019/2015: not required; Lifetime L80/B10 at 25°C: 50000; LED-Lifetime light source L70/B50 at 25°C: 50000; ETIM Gruppen-ID: ECOQ2892; With illuminant: No; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: No; Suitable for light line configuration: No; Suitable for workplace according to EN 12464-1: No; Material cover: Glass matt/satinized; With control gear: No; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: Yes; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: Yes; Dimming phase cut-off: Yes; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: Yes; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Light outlet: -; Degree of protection (NEMA): 2; Impact strength: IK03; Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: No; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: No; Covering of the luminaire with thermally insulating material possible: No; With air slots: No; Filament test according to IEC 60695-2-11: 750 °C - 30 s; Constant light output (CLO): Yes; Type of wiring: Ending; Photobiological safety according to EN 62471: RGO; Colour of light adjustable: Positions; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Exchangeable control gear: No; Suitable for lamp power in w: 10; Lamp type: LED not exchangeable; Emergency power supply integrated: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 50000; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: E; Luminous flux adjustable: No; Beam angle adjustable: No; Type of grid: Matt; Surface protection housing: Powder coating; Light sharing: Double asymmetric; Light distributor: Other; Type of control gear: Not required; Beam angle: Open beam/diffuse; Connection type: Other; Lamp holder: Other  
width: 100mm