

DOTLUX Wall light GUIDERound 8W 3000K

Order number: 5303-030070

- Decorative, flat wall light with glare-free light for staircase and path lighting
- Particularly insect-friendly lighting thanks to warm white LEDs and asymmetrical light distribution
- Robust, splash-proof aluminum housing with IP65 offers the best protection for outdoor use
- Through-wiring possible thanks to two large rubber cable grommets and quick-connect terminal
- Sustainable product design thanks to easily replaceable components
- EasyBase platform enables quick and easy installation
- Housing color similar to RAL 9005

Net luminous flux in lumens: 240; Lumen per watt: 30; Power consumption in watts: 8; Beam angle: 70; protection class (IP): IP65; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Power Factor: 0,9; Inrush current in A: 0; IK protection: IK08; Lumen per watt: 30; Protection class: I; Voltage type: AC; Housing colour: black; Switch cycles: > 100.000; Warranty in years: 3; similar to RAL-Colour: 9005; Energy efficiency class according to EU regulation 2019/2015: not required; ETIM Gruppen-ID: EC002892; Material cover: Glass transparent; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK08; Covering of the luminaire with thermally insulating material possible: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany; Energieeffizienzklasse der Lichtquelle einer Leuchte: F; Colour of light adjustable: No
diameter: 180mm