

DOTLUX Wall light Sixfold 6W 3000K white

Order number: 5992-030030

- This DOTLUX outdoor wall light is equipped with 6 light outlets (3 at the top and 3 at the bottom) to create an impressive play of light. With its asymmetrical lens, it provides particularly uniform and targeted illumination.
- The DOTLUX Sixfold is ideal for accent lighting and creates a pleasant atmosphere.
- The aluminum housing is not only robust, but also aesthetically pleasing. Whether you install it on the patio or at the front door, it will immediately enhance your outdoor area.
- Housing color similar to RAL 9016

Power consumption in watts: 6; Net luminous flux in lumens: 320; Lumen per watt: 53; Beam angle: 30x20; protection class (IP): IP65; Light color: white; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000; Color-rendering-index: CRI > 82; Power Factor: 0,8; IK protection: IK06; Lumen per watt: 53; Protection class: I; Voltage type: AC; Housing colour: white; Suited for emergency lighting: No; Warranty in years: 3; L80/B10: 60000; similar to RAL-Colour: 9005; Suitable for surface mounting: Yes; Suitable for mounting: No; Assortment: Proline; Energy efficiency class according to EU regulation 2019/2015: not required; Mounting location: Indoor + covered outdoor; Lifetime L80/B10 at 25°C: 60000; LED-Lifetime light source L70/B50 at 25°C: 90000; ETIM Group Identification Number: EC002892; With illuminant: Yes; Suitable for wall mounting: Yes; Suitable for suspended mounting: No; Suitable for ceiling mounting: No; Suitable for light line configuration: No; Suitable for workplace according to EN 12464-1: No; Material cover: Plastic, structured; With control gear: No; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: Yes; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: Yes; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: No; Light distributor: Focal lens; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK06; Luminaire with limited surface temperature, sign "D" according to EN 60598-2-24: No; Suitable for emergency lighting: No; With movement sensor: No; With light sensor: No; Covering of the luminaire with thermally insulating material possible: No; With air slots: No; Filament test according to IEC 60695-2-11: 750 °C - 30 s; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Exchangeable control gear: No; Lamp type: LED not exchangeable; Emergency power supply integrated: No; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Lifetime L70/B50 at 25°C: 90000; Lifetime L90/B10 at 25°C: 30000; BEG funding: Only relevant in Germany; Energy efficiency class of the light source of a luminaire: F; Light sharing: Asymmetric; Colour of light adjustable: No; Luminous flux adjustable: No; Beam angle adjustable: No; Light outlet: Direct/indirect; Beam angle: Medium beam 21-40°; Surface protection housing: Other; Type of control gear: Not required; Degree of protection (NEMA): Other
width: 94mm