

DOTLUX mirror light TRENDosensor 11W 3000/4000/5700K COLORselect

Order number: 4994-0FW140-B-Ware

- Modern, stylish design with integrated sensor with user-friendly on/off function
- Maximum illuminated area without visible screw Connections
- EASYbase platform allows easy and quick mounting
- Mounting on existing drill holes possible due to free area on base plate
- 2 cable inlets pre-installed (if required, individual inlets can be drilled into the aluminum base)
- Simply set your own desired light color, one part number - three light colors through COLORselect
- Sustainable product design through easily replaceable components

- Sensor with on/off function and daylight detection
- Following values are adjustable in steps:

- Range (up to 6m)
- Daylight sensor
- light duration

Power consumption in watts: 11; Net luminous flux in lumens: max. 1200; Beam angle: 140; protection class (IP): IP44; Input voltage: 220 - 240 V AC; Service life: approx. 50.000 h at 25°C; Color temperature in Kelvin: 3000/4000/5700; Color-rendering-index: CRI > 82; Power Factor: 0,7; Inrush current in A: 0; IK protection: IK08; Protection class: I; Switch cycles: > 100.000; Input voltage span: 220-240; Warranty in years: 0; Input voltage range luminaire: 220-240; Assortment: Proline; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: No; Dimming depending on control gear: No; No dim function: Yes; Colour consistency (McAdam ellipse): SDCM6; Impact strength: IK08; Dimming DALI-2: No; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0
width: 85mm