

**LED power supply CC 15-44W 300-1050mA 6-52V PUSH dimmable DALI-2 suitable for central battery through-wireable**

Order number: 5068-1

- The power supply is dimmable via DALI-2
- With the constant current technology (CC) it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 1%-100%
- The output current is adjustable: 300/350/400/450/500/550/600/650/700/750/800/850/900/950/1000/1050mA
- The power supply is set to 950mA by default
- Suitable for use in emergency lighting systems

Power consumption in watts: 15-44; protection class (IP): IP20; Input voltage: 176 - 240 V AC/DC; Output current in A: 0,35-1,05; Inrush current in A: 0; Tc temperature in °C: 90; Protection class: II; Output voltage: 6-52; Input voltage span: 176-264 AC / 170-275 DC; Warranty in years: 3; Dimming without dimmer: No; Input voltage range luminaire: 176-264 AC / 170-275 DC; ETIM Gruppen-ID: EC002710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: Yes; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: No; Dimming RF: No; Dimming Sine Wave Reduction: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: Yes; No dim function: No; Constant light output (CLO): No; Operation by Bluetooth: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Suitable for constant voltage: No; Suitable for DC-voltage (primary side): No; Suitable for constant current: Yes; Housing: Plastic housing; Dimming phase cut-on: No; Dimming GPRS: No; Pulse duration in µs: 0; BEG funding: Only relevant in Germany width: 57mm