

LED power supply CC 750mA 40W 30-50V incl. motion and daylight sensor

Order number: 4336

- Three different functions of the high-frequency sensor possible:
 - On/Off function to 100% light intensity via sensor, then 0% light intensity.
 - On/Off function to 100% luminous intensity via sensor with adjustable afterglow duration/power
 - Permanent basic brightness (20% / 35% luminosity) with additional On/Off function to 100% luminosity via sensor with adjustable afterglow duration
- In addition, the following values are adjustable in steps:
 - Range (up to 10 m)
 - daylight sensor - light duration
 - Afterglow duration (none to continuous)
 - Afterglow power (10% / 25%)

Power consumption in watts: 60; protection class (IP): IP20; Input voltage: 220 - 240 V AC; Tc temperature in °C: 50; Protection class: II; Suited for emergency lighting: No; Output voltage: 30 - 50 DC; Input voltage span: 220-240 AC; Dimming without dimmer: No; Input voltage range luminaire: 220-240 AC; ETIM Gruppen-ID: EC002710; Dimming 0-10 V: No; Dimming 1-10 V: No; Dimming DALI: No; Dimming DMX: No; Dimming DSI: No; Dimming potentiometer (integrated): No; Dimming LineSwitch: No; Dimming manufacturer's proprietary system: No; Dimming mains voltage modulation: No; Dimming phase cut-off: No; Dimming programmable: Yes; Dimming RF: No; Dimming Touch and Dim: No; Dimming Zigbee: No; Dimming with push-button: Yes; No dim function: No; Suitable for emergency lighting: No; Compatible with Casambi: No; Compatible with Apple HomeKit: No; Compatible with Google Assistant: No; Compatible with Amazon Alexa: No; IFTTT support available: No; Housing: Plastic housing; Dimming phase cut-on: No; Dimming GPRS: No; BEG funding: Only relevant in Germany
width: 35mm